

CONCEPT™ 3 CEILING FAN



Brushed Aluminium

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover)

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Wall Controller Speed Capacitor Values:

3.5µF & 2µF

Top of canopy cover to lowest point of the fan:

Approximately 330mm

Rotational Diameter:

1320mm (52") blade sweep

Ceiling to top side of the blade:

260mm

Motor:

16 Pole, 153mm x 18mm motor
Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Weight Including Packaging:

Complete fan: 9.35kg

Packaging Dimensions (mm):

Complete Fan: 605L x 288W x 300H

Motor Housing:

Materials: Die Cast Aluminium

Accessories (Supplied separately):

Remote Control
Extension Down Rod 26mm diameter (includes wire harness)
38° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses

Available Motor Housing Colours :

White, Brushed Aluminium and Matt Black

Blades: Dynamic Aerofoil

Sizes: 1320mm (52")

Materials: Injection moulded high temperature plastic

Blade Pitch: 10°

Warranty

2 years standard warranty "in home"

3 years extended warranty on motor only (excluding labour)

Available Blade Colours:

White, Silver and Matt Black

Extra Information:

Introduced into the HPI range in 2017

3 Speed wall controller

Reversible

Light Adaptable

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	HIGH	MED	LOW
RPMS	205	135	90
WATTS	58.5	24	12
AIRFLOW: CFM* / CMH*	7840 / 13320	4743 / 8059	2744 / 4662
EFFICIENCY[^]: (CFM / Watt) / (CMH / Watt)	134 / 228	198 / 336	229 / 389

* CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour.

[^] Efficiency measured as airflow rate per Watt.

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au