

INTERCEPT 2 WITHOUT LIGHT



Brushed Aluminium no light

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover)
(brushed aluminium not recommended for outdoors)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan

Approximately 330mm

Motor:

16 Pole, 153mm x 17mm motor
Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Die Cast Aluminium

Available Colours :

White, Black & Brushed Aluminium

Blades:

Sizes: 1320mm (52")
Materials: Plywood with painted finish
Blade Pitch: 12°

Available Colours:

White, Black & Brushed Aluminium

Extra Information

Introduced into the HPI range in 2014
3 Speed wall controller
Not light adaptable
Reversible

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

2µF & 3.5µF

Rotational Diameter:

1320mm (52") blade sweep

Ceiling to top side of the blade:

Approximately 223mm

Weight Including Packaging:

Complete fan: 7.2kg

Packaging Dimensions (cm):

Complete Fan: 60L x 28W x 29.5H

Accessories: (Supplied separately)

Remote Control
Extension down Rod (26mm diameter)
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses and suspended ceilings
1220mm (48") blades

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

| | HIGH | MED | LOW |
|--|---------------------|--------------------|--------------------|
| RPMS | 198 | 127 | 86 |
| WATTS | 60.90 | 27.10 | 15.10 |
| AIRFLOW[^]: USA(CFM) / AUS (CMH) | 7010 / 11911 | 4346 / 7384 | 2949 / 5010 |
| EFFICIENCY[^]: USA-ES / AUS-ES | 115 / 196 | 160 / 272 | 195 / 332 |

[^] Efficiency measured as airflow rate per watt.

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

INTERCEPT 2 WITH LIGHT



Brushed Aluminium with light

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover) (brushed aluminium not recommended for outdoors)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan

Approximately 400mm

Motor:

16 Pole, 153mm x 17mm motor
Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Die Cast Aluminium

Available Colours :

White, Black & Brushed Aluminium

Available integrated light options:

Twin E27 screw sockets.
R7s lamp holders (78mm lamp size)

Blades:

Sizes: 1320mm (52")
Materials: Plywood with painted finish
Blade Pitch: 12°

Available Colours:

White, Black & Brushed Aluminium

Extra Information

Introduced into the HPI range in 2014
3 Speed wall controller
Only Available with Light
Reversible

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

2µF & 3.5µF

Rotational Diameter:

1320mm (52") blade sweep

Ceiling to top side of the blade:

229mm

Weight Including Packaging:

Complete fan: 7.8kg

Packaging Dimensions (cm):

Complete Fan: 60L x 28W x 29.5H

Accessories: (Supplied Separately)

Remote Control
Extension down Rod 26mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses and suspended ceilings
1220mm (48") blades

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

| | HIGH | MED | LOW |
|---|---------------------|--------------------|--------------------|
| RPMS | 198 | 127 | 86 |
| WATTS | 60.90 | 27.10 | 15.10 |
| AIRFLOW[^]: USA(CFM) / AUS(CMH) | 7010 / 11911 | 4346 / 7384 | 2949 / 5010 |
| EFFICIENCY[^]: USA-ES / AUS-ES | 115 / 196 | 160 / 272 | 195 / 332 |

[^] Efficiency measured as airflow rate per watt.

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au